

Eagle Pure-Core® Pipe & Tubing

Superior Products from a Trusted Source



POLYETHYLENE PURE-CORE[®]

POLYETHYLENE PURE-CORE® BLUE



Eagle Pure-Core and Pure-Core Blue are relied upon by municipalities and independent contractors alike for water service distribution. Each is available in a variety of diameter and spool lengths.

Eagle Pure-Core[®] Blue Pipe and Tubing

- Pipe meets the requirements of ASTM D 2239 and AWWA C901.
- Tubing meets the requirements of ASTM D 2737 and AWWA C901 with Copper Tube Size (CTS) outside diameters.
- Material is high-density PE 3408, meeting cell class 345444 or 335444.
- Listed for potability to ANSI/NSF Standard 61.
- Natural core with blue exterior.
- Color-coded tags denote product and pressure rating for improved warehouse control.
- 50 year warranty

Eagle Pure-Core® Pipe

- Meets the requirements of ASTM D 2239.
- Material is medium-density PE 2406, meeting cell class 224343.
- Listed for potability to ANSI/NSF Standard 61.
- Natural core with carbon black exterior.
- Color-coded tags denote product and pressure rating for improved warehouse control.
- 50 year warranty

PWPipe is the largest producer of PVC pipe in western North America and our products are available from distributors throughout this geographic area. PWPipe products include PVC and polyethylene pipe and tubing for a variety of applications servicing the potable water, well casing, sewer, turf, agriculture, plumbing, communications, and electrical markets. Our manufacturing facilities in Oregon, Washington, California, Utah, and Nebraska assure on-time delivery.



N PERS

Pure-Core[®] Blue HDPE Pipe

	P.R. 200 psi, SIDR 7, Mandarin Tag Color								
Nominal Pipe Size (inches)	Approximate Outside Diameter (inches)	Average Inside Diameter (inches)	Minimum Wall Thickness (inches)	Approximate Weight (Ibs/100')	Standard Coil Lengths (feet)				
3⁄4	1.07	0.824	0.118	15	100-400				
1	1.37	1.049	0.150	25	100-300				
1 1⁄4	1.80	1.380	0.197	43	100-300				
1½	2.10	1.610	0.230	59	100-250				

Pure-Core[®] Blue HDPE Tubing

P.R. 200 psi, SDR 9, White Tag Color								
Nominal Pipe Size (inches)	Average Outside Diameter (inches)	Approximate Inside Diameter (inches)	Minimum Wall Thickness (inches)	Approximate Weight (Ibs/100')	Standard Coil Lengths (feet)			
1⁄2	0.625	0.47	0.069	5	100-400			
3⁄4	0.875	0.66	0.097	10	100-400			
1	1.125	0.85	0.125	17	100-300			
1 ¼	1.375	1.04	0.153	26	100-300			
1 ½	1.625	1.23	0.181	36	100-250			
2	2.125	1.62	0.236	62	100-200			

Pure-Core[®] MDPE Pipe – ASTM D2239 emium Grade Flexible NSF Liste Min. Wall Coil Nominal Pressure Approx. Average Approx. Tag SIDR Rating Pipe Size O. D. I. D. Thickness Weight Lengths Color (inches) (psi) (inches) (inches) (inches) (lbs/100') (feet) 9 100 Blue 0.77 0.622 0.069 7 100-400 1⁄2 7 125/160 0.81 0 622 0.089 9 100-400 Green 11.5 80 Goldenrod 0.98 0.824 0.072 9 100-400 3⁄4 9 100 Blue 1.02 0.824 0.092 12 100-400 7 125/160 Green 1.08 0.824 0.118 15 100-400 11.5 80 Goldenrod 1 24 1 049 0.091 14 100-300 9 100-300 1 100 Blue 1.30 1.049 0.117 19 7 125/160 Green 1.37 1.049 0.150 25 100-300 11.5 80 Goldenrod 1.64 1.380 0.120 25 100-300 11/4 9 100 Blue 1.71 1 380 0.153 32 100-300 7 125/160 Green 1.80 1.380 0.197 43 100-300 9 100 Blue 1.99 1.610 0.179 44 100-250 11/2 2 9 100 Blue 2.56 2.067 0.230 73 100-200

Note

PWPipe product specifications and warranties are continually updated. If more than 12 months have passed since the date of this brochure, call your PWPipe representative and ask about changes.

